MULTITEL MTE 270

Ente	Rev.	Descrizione	Data	Dis.	Contr.	Ap.AQ
MRK	2	EMISSIONE	18/09/20	F.Z.		
DIAGRAMMA - SCHEDA 54/2 - Rev. 0 - 15/12/00						

D61723

			230Kg	100Kg
P.T.T.=3500 kg	STABILIZZATORI COMPLETAMENTE ESTESI	SBRACCIO DI LAVORO	10,4 m ±5%	13,5 m ±5%
G.V.W.=3500 kg	FULLY EXTENDED STABILIZERS	WORKING OUTREACH	10,4 m ±5%	13,5 m ±5%
P.T.A.C.=3500 kg	STABILISATEURS COMPLETEMENT ETENDUS	DEPORT DE TRAVAIL	10,4 m ±5%	13,5 m ±5%
GES. GEWICHT=3500 kg	GANZ AUSGEFAHRENE STUTZEN	ARBEITSSTÜCKE	10,4 m ±5%	13,5 m ±5%



Macchina dotata di sistema di limitazione dello sbraccio a controllo di momento, le linee del grafico rappresentano le condizioni limite, ovvero con il carico massimo (carico nominale) e con il carico minimo (peso di una persona senza attrezzi - 80kg). Per ogni carico compreso tra questi due valori si ottiene una curva che sta tra le due linee tracciate.

Machine equipped with a movement control extension limit system. The graphic lines represent the limit conditions, meaning the maximum load (nominal load) and with a minimum load (weight of one person without tools - 80 kg). Every load between these two values obtains a curve that runs between the two marked lines.

Machine équipée d'un système de limitation de la portée à contrôle de moment, les lignes du graphique représentent les conditions limites, c'est-à-dire avec la charge maximum (charge nominale) et avec la charge minimum (poids d'une personne sans outils - 80 kg). Pour toute charge comprise entre ces deux valeurs, on obtient une courbe qui se situe entre les deux lignes tracées.

Die Maschine ist mit einem System zur Begrenzung der Ausladung mit Prüfmoment ausgestattet, die Grafiklinien stellen die Grenzbedingungen mit der maximalen Last (Nennlast) und der Mindestlast (Gewicht einer Person ohne Werkzeuge - 80 kg) dar. Für jede Last innerhalb dieser beiden Werte wird eine Kurve zwischen den beiden Linien erstellt.